| | | A: 1370 1260 max. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | 275 | ELECTION Packaging IP-MGBneo4/7770L T70 L B: max. 870 max. 800 of the second of t |
|--|---|---|-------------|--|
| Art.No: IP-MGBne | eo⁴/770 | - 1090 - | | 480.01 |
| Art.No: IP-MGBne Technical Data: External dimension L x W x H | | + | | P |
| Technical Data: | | + | ±70 | 634.89 |
| Technical Data: External dimension L x W x H | mm: A: 137(| + | ±70 | 634.89 |
| Technical Data: External dimension L x W x H Volume (I): | mm: A: 1370 770 I | + | ±70 | 634.89 |
| Technical Data: External dimension L x W x H Volume (I): Material body, material lid: | mm: A: 1370 770 I PE/PE | p±10 | ±70 | 634.89 |
| Technical Data: External dimension L x W x H Volume (I): Material body, material lid: Holding capacity (kg) | mm: A: 1370 770 I PE/PE | 1090 1090 1090 | ±70 | 634.89 |
| Technical Data: External dimension L x W x H Volume (I): Material body, material lid: Holding capacity (kg) Available colours: | mm: A: 1370 770 I PE/PE | 9±10 308 kg grey, blue, red, yellow | ±70 | 634.89 |
| Technical Data: External dimension L x W x H Volume (I): Material body, material lid: Holding capacity (kg) Available colours: Characteristics: | mm: A: 1370 770 I PE/PE SEN 840, RAL-GZ 95 | 9±10 308 kg grey, blue, red, yellow | B: max. 870 | C: max. 1370 |
| Technical Data: External dimension L x W x H Volume (I): Material body, material lid: Holding capacity (kg) Available colours: Characteristics: Container corresponds to: | mm: A: 1370 770 I PE/PE SEN 840, RAL-GZ 95 | 1090 1090 9±10 308 kg grey, blue, red, yellow | B: max. 870 | C: max. 1370 Extra equipment / Accessories Automatic lock |
| Technical Data: External dimension L x W x H Volume (I): Material body, material lid: Holding capacity (kg) Available colours: Characteristics: Container corresponds to: Travelling gear: | mm: A: 1370 770 I PE/PE kg green, g EN 840, RAL-GZ 95 4 x Ø -200 mm cast | 1090 1090 9±10 308 kg grey, blue, red, yellow | B: max. 870 | C: max. 1370 Extra equipment / Accessories Automatic lock Directional lock for castor wheel |

Loading quantities (Pcs / Approximate amount:)

On request

Labeling:

On the lid, on the body

*1) All specifications quoted are subject to change. We reserve the right to make changes to product design and specification. Dimension are stated according to DIN EN 840. Variations within the tolerances gives in the norm are possible.

*2) Extra equipment, accessories, as well as other colors are available at extra cost and on request









IPG Intelligent Packaging Group AB Skallabackavägen 24, 302 41 Halmstad, SWEDEN www.ip-group.se Växel: 035 102480 info@ip-group.se

qvalify ISO 14001 qvalify ISO 9001