<image/> <image/> <image/>		-	x: 1370 ±10 1260 ⁺²⁰ x. 1275 x. 1275	<image/> <section-header></section-header>
External dimension L x W x H mi	m: A: 1370±	10	B: max. 1190	C: max. 1470
Volume (I):	11101			
Material body, material lid:	PE/PE			
Holding capacity (kg)	kg L	440 kg		
Available colours:	green, gre	ey, blue, red, yell	ow	
Characteristics:				Extra equipment / Accessories
Container corresponds to:	EN 840, RAL-GZ 951/	1		Automatic lock
Travelling gear:	$4x\text{\emptyset}$ -200 mm castor wheels, standard equipt with wheel stop			Directional lock for castor wheel
Receiver:	Comb lift			Triangular lock
Prepared for transponder	Yes			Noise insulation plugs Glas aperture

Loading quantities (Pcs / Approximate amount:)

On request

Labeling:

On the lid, on the body

*1) All specifications quoted are subject to change. We reserve the right to make changes to product design and specification. Dimension are stated according to DIN EN 840. Variations within the tolerances gives in the norm are possible.

*2) Extra equipment, accessories, as well as other colors are available at extra cost and on request









IPG Intelligent Packaging Group AB Skallabackavägen 24, 302 41 Halmstad, SWEDEN www.ip-group.se Växel: 035 102480 info@ip-group.se

qvalify ISO 14001 qvalify ISO 900